

RIMS

INDEX		Cross References	PAGE
GENERAL NOTES	NOTES GÉNÉRALES	ALLGEMEINE BEMERKUNGEN	
1. Strength			R.4
2. Rim Contours			R.4
3. Valve Holes			R.4
4. Rim Measurements			R.5
5. Rim Markings			R.5, R.6
6. Drop Centre Rims			R.7
7. Multipiece Rims			R.7
8. Openings in Detachable Spring Flanges			R.7
PASSENGER CARS, LCVs AND TRAILERS	VOITURES PARTICULIÈRES, VÉHICULES UTILITAIRES LÉGERS ET REMORQUES	PERSONENKRAFTWAGEN, LEICHT LKWs UND ANHÄNGER	
9. 5° Drop-Centre Rims Diameter Code 10 to 30			R.8 to R.13
9.1 Basic		'B and J'	R.8 to R.10
9.2 Alternative J-Profile		'J-N'	R.11
9.3 Alternative J-Profile for Flexible Wheels "FL"		'J-FL'	R.12 to R.13
10. Contours for Bead retention on 5° Drop-Centre Rims			R.13 to R.17
10.1 General Notes			R.13
10.2 Hump		'H'	R.14
10.3 Flat Hump		'FH'	R.15
10.4 Extended Hump		'EH2'	R.16
10.5 Extended Hump plus		'EH2+'	R.17
11. Metric "A" Rims			R.18
COMMERCIAL VEHICLES	VÉHICULES UTILITAIRES	NUTZFAHRZEUGE	
12. 15° Drop-Centre Rims Width	Codes 5.25 to 9.75		R.19
13.	Codes 11.75 and Larger		R.20
14. 15° Drop-Centre Rims with Hump			R.21
14.1 Alternative Flange Contours for 15° Drop-Centre Rims			R.22
15. 5° on Drop-Centre Rims			R.23
16. Key Dimensions for TPMS on Drop-Centre Rims			R.24
16.1. Steel			R.24
16.2. Aluminium			R.25
17. 5° Tapered Rims	5.0 to 14.0V 5°		R.26
18. Flat Base Rims	S, T, V, W for 4.33 R	see §33	R.27
19. Semi-Drop Centre Rims	E, F, G, H for 8.00 TG to 16	see §39	R.28
5° Drop-Centre Rims	for Contour Gauge for B, J for E, F, 9, 11, 12, 13, 13.0	see §43 see §9 see §21	
Divided Rims	for W, DW, TW and Knurling specification for 3.00 D for 3.25I, 5.00S	see §22 see §31.2 see §34	



INDEX		Cross References	PAGE
AGRICULTURAL EQUIPMENTS	EQUIPEMENT AGRICOLE	LANDWIRTSCHAFTLICHE GERAETE	
20. Divided Rims	4.00E, 5.00F, 5.50F for 1.50, 2.10, 2.15, 2.50C, 3.50A	see §31.2	R.29
21. Drop-Centre Rims	E, F, I, JA, LB, 9, 9.00, 11, 12, 13, 13.0, 13.00, 14, 16.00 for B, J for 2.15, 2.50A, 2.50C, 3.00D, 3.50D, 5.50A, 7.00A	see §9 see §31.1	R.30, R.31
22.	W, DW, TW and Knurling specifications		R.32 to R.35
23.	DHB 27 x 32		R.36
24. 5° Drop-Centre Rim	DD (L) Rim Contour		R.37
25. 15° Drop-Centre	AG contour		R.38
26. Contours for Bead retention on AG 15° Drop-Centre Rims Semi-Drop Centre	for 12, 13, 16	see §39	R.39
CYCLES	CYCLES	FAHRRADER	
27. General Notes			R.40
27.1 Rims Contours			R.40
27.2 Rims Measurement			R.40
27.3 Diameter of Bead Seat Rims for Cycles			R.41
28. Cycle rims for tubular tyres			R.42
29. Cycle rims for regular (tube or tubeless) tyres			R.43
29.1 Crotchet Type Rims			R.43
29.2 Marking			R.43
29.3 Air-tight crotchet type rims for tubeless cycle tyres			R.44
29.4 Straight-side type rims			R.45
29.5 Air-tight straight-side type rims for tubeless cycle tyres			R.46
MOTORCYCLES	MOTOCYCLETES	KRAFTRAEDER	
30. Motorcycles and Scooters			R.47
30.1 Drop-Centre Rims with Cylindrical Beat Seats			R.48 to R.50
30.2 Drop-Centre Rims with 5° Tapered Beat Seats – MT Type			
31. Miscellaneous Applications			R.51, R.52
31.1 Drop-Centre Rims for Miscellaneous Applications			R.53
31.2 Divided Rims for Miscellaneous Applications			
INDUSTRIAL VEHICLES AND LIFT TRUCKS	VÉHICULES INDUSTRIELS ET CHARIOTS À ÉLEVATEUR	INDUSTRIEFAHRZEUGE UND STAPLER	
For 15° Drop-centre Rims		see §12 - §13 - §14	
32. 5° Tapered Rims	3.00D, 4.00E, 6.00E, 5.00F, 5.50F, 6.50F, 5.00S, 8.00G, 10.00G for 5.0-15 to 9.75-15	see §17	R.54
33. Flat Base Rims	3.11F, 3.75P, 4.33R, 6.00S for 5.00S, 6.00T	see §18	R.55
34. 5° Tapered Bead Seat Rims Divided Type	3.25I, 3.75I, 5.00S for 2.10, 2.50C for 5.00F	see §31.2 see §20	R.56
35. Rims for Solid tyres on pneumatic shaped rims mounted without locking rings			R.57
36. Rims for Industrial tyres for nominal diameter code 25 and above			R.58

INDEX		Cross References	PAGE
EARTHMOVING EQUIPMENT	ENGINS DE GÉNIE CIVIL	ERDBEWEGUNGS-MASCHINEN	
37. Full Tapered Bead Seat Rims For 5° Tapered Rims		see §17	R.59 to R.63
38. CR Single Piece 5° DC Rims For Mobile Cranes			R.64
39. Semi-Drop Centre Rims 8.00TG to 16.00T			R.65, R.66
40. Transverse knurling details			R.67
41. 5° Drop-Centre Rims 9.00/1.5, 12.00/1.3, 13.00/1.4, 14.00/1.3, 14.00/1.5, 16.00/1.3			R.68
42. Flat Base Rims for 13, 13.0 11.25/2.5 for 5.00S, 6.00T, 10.00V, 10.00W		see §21	R.69
		see §18	
RIM INSPECTION	INSPECTION JANTES	FELGEN PRÜFUNG	
43. Passenger cars and Trailers - 5° Drop center Rims Contour Gauge			R.70
44. Agricultural Equipments - Recommended Inspection Gauges 5° Drop-Centre Rims			R.71
45. Cycles - Gauges, tape and procedure			R.72 to R75
46. Cycle - Measurement of Circumference of Parallel Bead Seat Rims			R.76
DIMENSIONS FOR RIM MEASUREMENT	DIMENSIONS POUR MESURES DE JANTES	MASSE FÜR FELGENMESSUNGEN	
47. Tapered Bead Seat Rims			R.77 to R.79
48. Metric "A" Rims			R.79
49. 15° Drop-Centre Rims			R.80
50. Rims with Two Demountable Flanges			R.80
Notes	Notes	Bemerkungen	R.81 to R.83