

# DESIGN GUIDE

## Earthmoving Equipment Tyres

INDEX	PAGE
Tyre size designation	EM.2
Maximum envelope for grown tyres in service	EM.2
Calculation of tyre dimensions	EM.3
Nomenclature	EM.3
Theoretical rim width ( $a_1$ )	EM.3
Measuring rim width ( $a$ )	EM.3
Design section width ( $s$ )	EM.3
Minimum section width ( $s_{min}$ )	EM.4
Maximum overall width in service ( $s_G$ )	EM.4
Design section height ( $h$ )	EM.4
Design overall diameter ( $d$ )	EM.4
Maximum and minimum new tyre overall diameter	EM.4
Maximum overall diameter in service ( $d_G$ )	EM.4
Minimum dual spacing ( $SP_{min}$ )	EM.4
Tyres with deep and extra-deep tread pattern depths	EM.4
Tread code and design tread depth	EM.5
Nominal section width steps	EM.6
Rims – Stepping of nominal rim diameter codes	EM.7
Guidelines for calculation of minimum flap width	EM.7
Guidelines on harmonization of load capacities	EM.7
Guidelines for inflation pressure tolerances	EM.7
Guidelines for maximum overall diameter	EM.7
Guidelines for load capacities in transport application	EM.8
Load speed table for mobile crane tyres	EM.9

D  
G

E