

DESIGN GUIDE

Rims

INDEX	PAGE
GENERAL	
Notes	RM.1
Guidelines for specified diameters of future rims	RM.2
Contour changes of drop centre rims	RM.2
RIMS FOR PASSENGER CAR TYRES	
Rim Width Steps	RM.3
Light Alloy Rims for Racing Applications – Rim dimensions	RM.3
RIMS FOR COMMERCIAL VEHICLE TYRES	
15° Drop-Centre Rims (width codes 5.25 to 9.75)	RM.4
15° Drop-Centre Rims (width codes 10.50 and larger)	RM.4
RIMS FOR AGRICULTURAL AND IMPLEMENT TYRES	
Rim Width Steps	RM.5
RIMS FOR EARTHMOVING EQUIPMENT TYRES	
Sealing Ring Grooves	RM.6
DIMENSIONS FOR RIM MEASUREMENT	
Measurement of 15° Drop-Centre Rims	RM.7
Measurement of Tapered Bead Seat Rims	RM.8
Measurement of Cycle and Moped Rims	RM.9
COMPARISON OF FLANGE HEIGHT SUFFICES IN STANDARDS	RM.10

D
G

GENERAL NOTES	NOTES GÉNÉRALES	ALLGEMEINE BEMERKUNGEN
STRENGTH	RESISTANCE	FESTIGKEIT
Consult rim and wheel manufacturers for confirmation of the strength of the rim/wheel for the intended service.	Consultez les fabricants de jantes et de roues pour vous assurer que la jante et la roue ont une résistance suffisante pour l'utilisation envisagée.	Konsultieren Sie die Felgen- und Räderhersteller zwecks Bestätigung der Felgen-/Rad-Festigkeit für den beabsichtigten Einsatz.